



ME 65 Super-Cardioid Microphone

The ME 65 is a super-cardioid microphone head designed for use with the K6 and K6P powering modules. It is especially suited to vocal and speech applications. Matt black, anodised, scratch-resistant finish.

Features—Benefits

- Excellent directivity across whole frequency range
- Frequency-independent super-cardioid pick-up pattern—ensures excellent feedback rejection
- Extremely high maximum sound pressure level
- High sensitivity
- Wide frequency range
- Integral pop filter

Technical Data

Pick-up pattern	super-cardioid
Frequency response	40–20,000 Hz \pm 2.5 dB
Sensitivity (free field, no load) (1 kHz)	10 mV/Pa \pm 2.5 dB
Nominal impedance	200 Ω (with K6)
Min. terminating impedance	1000 Ω (with K6)
Equivalent noise level	
A-weighted (DIN IEC 651)	20 dB
CCIR-weighted (CCIR 468-3)	30 dB
Max. SPL (1 kHz)	142 dB (THD = 3 %)
Dimensions in inches	1.73 x 5.15
Weight	2.82 oz

Optional Accessories

Foam windshield	MZW 65 Pro
-----------------	------------

Architect's Specifications

The unit shall be a super-cardioid microphone head suitable for K6 and K6P powering modules. The frequency response shall be 40 Hz–20,000 Hz, with sensitivity (free field, no load) of 10 mV/Pa \pm 2.5 dB at 1 kHz. The nominal impedance shall be 200 Ω (with K6), and min. terminating impedance of 1000 Ω (with K6). The dimensions shall be 1.73 x 5.15 inches, and weight 2.82 oz. The unit shall be a Sennheiser ME 65.

Sennheiser Electronic Corporation, 1 Enterprise Drive, Old Lyme, CT 06371

Telephone: 860-434-9190 • Fax: 860-434-1759 • Web: <http://www.sennheiserusa.com>

Sennheiser Mexico: Av. Xola 613, PH6, Col. Del Valle 03100, Mexico, DF. Telephone: (525) 639-0956. Fax: (525) 639-9482

Sennheiser Canada: 221 Labrosse Ave, Pte-Claire, PQ H9R 1A3. Telephone: 514-426-3013. Fax: 514-426-3953

Manufacturing Plant: Am Labor 1, 30900 Wedemark, Germany